



### ROLAIR® STANDARD FEATURES

**PUMP:** ROLAIR® Quality, Heavy Duty, Single Stage, Ball Bearings, Metal Filter with Silencer, Fan-Cooled, Fixed Rotation Speed, Stainless-Steel Reed Valves and Splash Lubrication Ensure Longer Life.

**ENGINE:** 118 cc (GX120) Honda, Cast-Iron Cylinder Sleeve, Overload Valves, On/Off Switch, Dual-Element Air Cleaner, Electronic Ignition and Low-Oil Control.

### SPECIFICATIONS

MODEL	HONDA ENGINE RATING	# OF CYLS.	CU. FT. DISPLACED	CU. FT. DELIVERED @ 90 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H) (INCHES)	APPROX. SHIPPING WT. (LB.)
GD4000PV5H	118 cc (GX120)	1	8.3	4.6	4.5	22 x 16 x 16	72

### STANDARD EQUIPMENT

- Unique Synchro-Balanced Coupling
- Air Line Regulator and Pressure Gauge
- Universal Quick-Disconnect with Plug
- Automatic Pilot Valve Operation
- Pressure Gauge 0-200 in 5 lb. Graduations
- Safety Relief Valve
- Automatic Engine Throttle for Economy and Long Service Life